

| | | | |
|--------------------|---------------------|------------|------------|
| Company: | | Page: | 1 |
| Address: | | Specifier: | |
| Phone Fax: | | E-mail: | |
| Design: | Rebar - 11 Jan 2024 | Date: | 11.01.2024 |
| Rebar application: | | | |

Specifier's comments:

1. Input data

General

| | |
|--|----------------------------|
| Design method | EN 1992-1-1:2004 + AC:2010 |
| Consider the effect of ΔF_{Td} | yes |
| Verification of interface shear | no |
| Consider compression reinforcement for CSD | no |
| Application type | Beam to wall |
| Continuous in X | yes |
| Loading type | Static |
| Design for yield | no |
| Design working life | 50 years |

**Product**

| | |
|-------------------------|--|
| Mortar | HIT-RE 500 V4 |
| Item number | 2287557 HIT-RE 500 V4 (adhesive) |
| UK Technical Assessment | UKTA-0836-22/6577 |
| Issued | 28.03.2023 |
| Installation | Hammer drilling (HD), Installation Condition: Dry Concrete |
| Drilling direction | Drilling aid is used (this improves the angle of drilling) |

Material and Geometry

| | |
|--|--|
| Existing concrete | C40/50, $f_{ck} = 40 \text{ N/mm}^2$ |
| New concrete | C40/50, $f_{ck} = 40 \text{ N/mm}^2$ |
| Joint roughness | Rough |
| Interface between new and old concrete | Rectangular cross section, width = 850 mm, height = 2,000 mm |
| Length of existing concrete | 1,200 mm |
| Temperature | During installation: from 5°C to 20°C; During service: 20 °C / 20 °C (short / long term) |
| Concrete reinforcement | Wide |

Post-installed rebar




| | | | |
|--------------------|---------------------|------------|------------|
| Company: | | Page: | 2 |
| Address: | | Specifier: | |
| Phone Fax: | | E-mail: | |
| Design: | Rebar - 11 Jan 2024 | Date: | 11.01.2024 |
| Rebar application: | | | |


| | Diameter | Coordinate Y | Bond | f_{yk} | Drilling length (l_v) |
|----------------|-----------------|---------------------|-------------|--------------------------|--|
| Top layer 1 | 32mm | 855 mm | Good | 500.00 N/mm ² | 320 mm |
| Top layer 2 | 32mm | 675 mm | Good | 500.00 N/mm ² | 320 mm |
| Bottom layer 1 | 32mm | -835 mm | Good | 500.00 N/mm ² | 584 mm |
| Bottom layer 2 | 32mm | -655 mm | Good | 500.00 N/mm ² | 584 mm |

1.1. Geometry & Loading


Geometrical dimensions in [mm]. Loading values in [kN, kNm]



1.2. Cross section view



1.3. Side section view



| | | | |
|--------------------|---------------------|------------|------------|
| Company: | | Page: | 6 |
| Address: | | Specifier: | |
| Phone Fax: | | E-mail: | |
| Design: | Rebar - 11 Jan 2024 | Date: | 11.01.2024 |
| Rebar application: | | | |

2. Loads

2.1. Load combination and Geometry

| LC | Load type | V _y [kN] | N [kN] | M _x [kNm] | Design Method | Max drill length l _v [mm] | Max. Utilization [%] |
|---------------|-----------|------------------------|-----------|-------------------------|---------------|---|-------------------------|
| Combination 1 | Static | 3,400.000 | 0.000 | 0.000 | EN1992-1-1 | 584.377 | 89 |

| | | | |
|--------------------|---------------------|------------|------------|
| Company: | | Page: | 7 |
| Address: | | Specifier: | |
| Phone Fax: | | E-mail: | |
| Design: | Rebar - 11 Jan 2024 | Date: | 11.01.2024 |
| Rebar application: | | | |

3. Overview of results

3.1. References


[1] EN 1992-1-1:2011 (01/2011): Eurocode 2: Design of concrete structures - Part 1-1: General rules and rules for buildings

3.2. Cross-section verification

| Description | Variable | Value |
|--|----------|--------------------------|
| Post-Installed Rebar diameter | ϕ | 32 mm |
| Reinforcement yield strength, post installed | f_{yk} | 500.00 N/mm ² |
| Concrete compressive strength, existing | f_{ck} | 40.00 N/mm ² |
| Concrete compressive strength, new | f_{ck} | 40.00 N/mm ² |
| Member height | h | 2,000 mm |
| Member width | b | 850 mm |

The determination of the load bearing capacity of the reinforced concrete member is performed assuming the Bernoulli Hypothesis ("plane sections remain plane").

For the (compressed) concrete the following stress-strain relationship (parabola-rectangle diagram) is used.



$$\sigma_c = f_{cd} \cdot \left[1 - \left(1 - \frac{\epsilon_c}{\epsilon_{c2}} \right)^n \right] \text{ for } 0 \leq \epsilon_c \leq \epsilon_{c2} \quad [1] \text{ Eq. (3.17)}$$

$$\sigma_c = f_{cd} \text{ for } \epsilon_{c2} \leq \epsilon_c \leq \epsilon_{cu2} \quad [1] \text{ Eq. (3.18)}$$

$$f_{cd} = \frac{\alpha_{cc} \cdot f_{ck}}{\gamma_c} \quad [1] (3.15)$$

The design stress-strain diagram for reinforcing steel (in tension and compression) is assumed to be bi-linear with a horizontal top branch.

| | | |
|-----------------|-----------------------------|--|
| f_{yd} | $= \frac{f_{yk}}{\gamma_s}$ | design yield stress |
| ϵ_{yd} | $= \frac{f_{yd}}{E_s}$ | design strain at yielding of steel reinforcement |
| ϵ_{ud} | | design ultimate strain for steel reinforcement |

| f_{ck} [N/mm ²] | α_{cc} [-] | γ_c [-] | f_{cd} [N/mm ²] | ϵ_{c2} [-] | ϵ_{cu2} [-] |
|-------------------------------|-------------------|----------------|-------------------------------|---------------------|----------------------|
| 40.00 | 0.850 | 1.500 | 22.67 | 0.002 | 0.0035 |

| f_{yk} [N/mm ²] | γ_s [-] | f_{yd} [N/mm ²] | E_s [N/mm ²] | ϵ_{yd} [-] | ϵ_{ud} [-] |
|-------------------------------|----------------|-------------------------------|----------------------------|---------------------|---------------------|
| 500.00 | 1.150 | 434.78 | 200,000.00 | 0.002 | 0.020 |

Input data and results must be checked for conformity with the existing conditions and for plausibility!

PROFIS Engineering (c) 2003-2024 Hilti AG, FL-9494 Schaan Hilti is a registered trademark of Hilti AG, Schaan

| | | | |
|--------------------|---------------------|------------|------------|
| Company: | | Page: | 8 |
| Address: | | Specifier: | |
| Phone Fax: | | E-mail: | |
| Design: | Rebar - 11 Jan 2024 | Date: | 11.01.2024 |
| Rebar application: | | | |


Additional tension force due to shear load

$$\Delta F_{td} = F_{Ed} = |V_{Ed}| \cdot \frac{a_l}{z} \quad [1] \text{ Eq. 9.3 and Section 9.2.1.3 (2)}$$

$$a_l = \frac{z \cdot (\cot \Theta - \cot \alpha)}{2} \quad [1] \text{ Eq. 9.2}$$

| | | | | | |
|---------------------------------|--------------------------------|---------------------------------------|--------------------------------|--|----------------------------|
| V_{Ed} [kN] | Θ [°] | $\cot \Theta$ [-] | α [°] | $\cot \alpha$ [-] | z [mm] |
| -3,400.000 | 42.5 | 1.091 | 90.0 | 0.000 | 1,571 |
| a_l [mm] | | $\frac{a_l}{z}$ [-] | | ΔF_{td} [kN] | |
| 857 | | 0.546 | | 1,855.224 | |

Rebar arrangement and diameter at the interface; see figure below



Resulting rebar forces

Force (+Tension, -Compression)

- Layer BottomLayer1 contains rebars 10-12
- Layer BottomLayer2 contains rebars 7-9
- Layer TopLayer1 contains rebars 1-3
- Layer TopLayer2 contains rebars 4-6

| Layer | Tension Force [kN] | Additional tension force due to shear load (ΔF_{td}) [kN] | Total Force [kN] |
|--------------|--------------------|---|------------------|
| TopLayer1 | - | - | - |
| TopLayer2 | - | - | - |
| BottomLayer2 | - | 927.612 | 927.612 |
| BottomLayer1 | - | 927.612 | 927.612 |

| | |
|---|------------------------|
| max. concrete compressive strain: | 0.000 ‰ |
| max. concrete compressive stress: | 0.00 N/mm ² |
| resulting tension force in (x/y) = (0.000/0.000): | 0.000 kN |
| resulting compression force in (x/y) = (0.000/0.000): | 0.000 kN |
| inner lever arm z = | - mm |

| | | | |
|--------------------|---------------------|------------|------------|
| Company: | | Page: | 9 |
| Address: | | Specifier: | |
| Phone Fax: | | E-mail: | |
| Design: | Rebar - 11 Jan 2024 | Date: | 11.01.2024 |
| Rebar application: | | | |

4. Rebar design in tension ([1] Section 8.4 , 8.7)

4.1. Steel verification and anchorage length determination

Input

| Description | Variable | Value |
|--|----------------|---------------------------|
| Characteristic concrete compressive strength, existing | f_{ck} | 40.00 N/mm ² |
| Characteristic concrete tensile strength (5%-fractile), existing | $f_{ctk;0.05}$ | 2.456 N/mm ² |
| Partial material safety factor | γ_c | 1.500 |
| Coefficient for long-term effects on the tensile strength | α_{ct} | 1.000 |
| Design concrete tensile strength, existing | f_{ctd} | 1.637 N/mm ² |
| Rebar diameter, Post-installed | ϕ | 32.000 mm |
| Reinforcement yield strength | f_{yk} | 500.000 N/mm ² |
| Partial material safety factor | γ_s | 1.150 |
| Shape of rebar influence ([1] Table 8.2) | α_1 | 1.000 |
| Concrete cover influence ([1] Table 8.2) | α_2 | 0.700 |
| Transverse pressure influence ([1] Table 8.2) | | |
| Transverse pressure | p | 0.00 N/mm ² |
| | α_5 | 1.000 |

Governing loading situation

The results presented in the following are valid for the governing loading situation:

The design is performed based on the results of the cross-section analysis (incl. additional tension forces due to shear loads)

Installation/Drill length results

$$l_v \geq l_{bd}$$

Layer BottomLayer1 contains rebars 10-12

Layer BottomLayer2 contains rebars 7-9

Layer TopLayer1 contains rebars 1-3

Layer TopLayer2 contains rebars 4-6

| Layer | ϕ [mm] | l_{bd} [mm] | l_v [mm] |
|--------------|----------------|------------------|---------------|
| BottomLayer1 | 32 | 584 | 584 |
| BottomLayer2 | 32 | 584 | 584 |
| TopLayer1 | 32 | 320 | 320 |
| TopLayer2 | 32 | 320 | 320 |

Steel verification

$$F_{Ed} \leq F_{yd} = \frac{A_s \cdot f_{yk}}{\gamma_s}$$

| | | | |
|--------------------|---------------------|------------|------------|
| Company: | | Page: | 10 |
| Address: | | Specifier: | |
| Phone Fax: | | E-mail: | |
| Design: | Rebar - 11 Jan 2024 | Date: | 11.01.2024 |
| Rebar application: | | | |

| Layer | F_{Ed} [kN] | ϕ [mm] | γ_s [-] | A_s [mm ²] | F_{yd} [kN] | Utilisation [%] | Status |
|-----------------------------|------------------|----------------|-------------------|-----------------------------|------------------|--------------------|--------|
| Post-Installed BottomLayer1 | 309.204 | 32 | 1.150 | 804 | 349.673 | 89 | Ok |
| Post-Installed BottomLayer2 | 309.204 | 32 | 1.150 | 804 | 349.673 | 89 | Ok |
| Post-Installed TopLayer1 | 0.000 | 32 | 1.150 | 804 | 349.673 | 0 | Ok |
| Post-Installed TopLayer2 | 0.000 | 32 | 1.150 | 804 | 349.673 | 0 | Ok |

Anchorage length

$$l_{bd} = \alpha_1 \cdot \alpha_2 \cdot \alpha_3 \cdot \alpha_4 \cdot \alpha_5 \cdot l_{b,rqd} \geq l_{b,min} \quad [1] \text{ Eq. (8.4)}$$

$$l_{b,rqd} = \frac{\phi}{4} \cdot \frac{\sigma_{sd}}{f_{bd}} \quad [1] \text{ Eq. (8.3)}$$

$$l_{b,min} = \max(0.3 \cdot l_{b,rqd}, 10 \cdot \phi, 100\text{mm}) \quad [1] \text{ Eq. (8.6)}$$

$$\sigma_{sd} = \frac{F_{Ed}}{A_s}$$

$$f_{bd} = 2.25 \cdot \eta_1 \cdot \eta_2 \cdot f_{ctd} \quad [1] \text{ Eq. (8.2)}$$

$$\eta_1 = 1.0 \text{ for good bond conditions} \quad [1] \text{ Section 8.4.2 (2)}$$

$$\eta_1 = 0.7 \text{ for all other cases}$$

$$\eta_2 = 1.0 \text{ for rebars with } \phi \leq 32\text{mm} \quad [1] \text{ Section 8.4.2 (2)}$$

$$\eta_2 = \frac{(132-\phi)}{100} \text{ for rebars with } \phi > 32\text{mm}$$

$$f_{ctd} = \frac{\alpha_{ct} \cdot f_{ctk;0.05}}{\gamma_c} \quad [1] \text{ Eq. (3.16)}$$

$$f_{ctk;0.05} = 0.7 \cdot f_{ctm} = 0.7 \cdot 0.3 \cdot f_{ck}^{\frac{2}{3}} \quad [1] \text{ Table (3.1)}$$

Post-installed rebars

In case of post-installed rebars, use $f_{bd,PIR}$ in [1] Eq. (8.3)

$$f_{bd,PIR} = k_b \cdot f_{bd}$$

$$k_b \text{ bond efficiency factor from UKTA-0836-22/6577}$$

$$l_{0,min} = \alpha_{lb} \cdot l_{0,min}$$

$$\alpha_{lb} \text{ amplification factor from UKTA-0836-22/6577}$$


Influencing factor (α_i) equations

Concrete cover


$$0.70 \leq \alpha_2 = 1 - 0.15 \cdot \frac{(c_d - \phi)}{\phi} \leq 1.00 \quad [1] \text{ Table 8.2}$$

Company:
 Address:
 Phone | Fax: |
 Design: Rebar - 11 Jan 2024
 Rebar application:


Page: 11
 Specifier:
 E-mail:
 Date: 11.01.2024



Straight bars
 $c_d = \min\left(\frac{a}{2}, c_1, c\right)$



Bent or hooked bars
 $c_d = \min(c_1, c)$



Looped bars
 $c_d = c$

Transverse pressure

$$0.7 \leq \alpha_5 = 1 - 0.04 \cdot p \leq 1.00 \quad [1] \text{ Table 8.2}$$

Combination limit

$$\alpha_{2,3,5} = \max(\alpha_2 \cdot \alpha_3 \cdot \alpha_5; 0.7) \quad [1] \text{ Eq. (8.5)}$$

| Layer | F_{Ed} [kN] | ϕ [mm] | A_s [mm ²] | σ_{sd} [N/mm ²] | η_1 [-] | η_2 [-] | f_{ctd} [N/mm ²] |
|-----------------------------|------------------|----------------|-----------------------------|---------------------------------------|-----------------|-----------------|-----------------------------------|
| Post-Installed BottomLayer1 | 309.204 | 32 | 804 | 384.46 | 1.000 | 1.000 | 1.637 |
| Post-Installed BottomLayer2 | 309.204 | 32 | 804 | 384.46 | 1.000 | 1.000 | 1.637 |
| Post-Installed TopLayer1 | 0.000 | 32 | 804 | 0.00 | 1.000 | 1.000 | 1.637 |
| Post-Installed TopLayer2 | 0.000 | 32 | 804 | 0.00 | 1.000 | 1.000 | 1.637 |

| Layer | k_b [-] | f_{bd} [N/mm ²] | $f_{bd,PIR}$ [N/mm ²] | α_{lb} [-] | $l_{b,rqd}$ [mm] | $l_{b,min}$ [mm] | c_d [mm] |
|-----------------------------|--------------|----------------------------------|--------------------------------------|----------------------|---------------------|---------------------|---------------|
| Post-Installed BottomLayer1 | 1.000 | 3.68 | 3.68 | 1.000 | 835 | 320 | 139 |
| Post-Installed BottomLayer2 | 1.000 | 3.68 | 3.68 | 1.000 | 835 | 320 | 139 |
| Post-Installed TopLayer1 | 1.000 | 3.68 | 3.68 | 1.000 | 0 | 320 | 139 |
| Post-Installed TopLayer2 | 1.000 | 3.68 | 3.68 | 1.000 | 0 | 320 | 139 |

| Layer | α_1 [-] | α_2 [-] | α_3 [-] |
|-----------------------------|-------------------|-------------------|-------------------|
| Post-Installed BottomLayer1 | 1.000 | 0.700 | 1.000 |
| Post-Installed BottomLayer2 | 1.000 | 0.700 | 1.000 |
| Post-Installed TopLayer1 | 1.000 | 1.000 | 1.000 |
| Post-Installed TopLayer2 | 1.000 | 1.000 | 1.000 |

Input data and results must be checked for conformity with the existing conditions and for plausibility!

PROFIS Engineering (c) 2003-2024 Hilti AG, FL-9494 Schaan Hilti is a registered trademark of Hilti AG, Schaan

| | | | |
|--------------------|---------------------|------------|--------------|
| Company: | | Page: | 12 |
| Address: | | Specifier: | |
| Phone Fax: | | E-mail: | |
| Design: | Rebar - 11 Jan 2024 | Date: | 11. 01. 2024 |
| Rebar application: | | | |

| Layer | α_4 [-] | p [N/mm ²] | α_5 [-] | $\alpha_{2,3,5}$ [-] | l_{bd} [mm] |
|-----------------------------|-------------------|-----------------------------|-------------------|-------------------------|------------------|
| Post-Installed BottomLayer1 | 1.000 | 0.00 | 1.000 | 0.700 | 584 |
| Post-Installed BottomLayer2 | 1.000 | 0.00 | 1.000 | 0.700 | 584 |
| Post-Installed TopLayer1 | 1.000 | 0.00 | 1.000 | 1.000 | 320 |
| Post-Installed TopLayer2 | 1.000 | 0.00 | 1.000 | 1.000 | 320 |

| | | | |
|--------------------|---------------------|------------|------------|
| Company: | | Page: | 13 |
| Address: | | Specifier: | |
| Phone Fax: | | E-mail: | |
| Design: | Rebar - 11 Jan 2024 | Date: | 11.01.2024 |
| Rebar application: | | | |

5. Warnings

This design exclusively considers the load transfer with post-installed rebars at the interface between new and existing concrete.

Load distribution to the rebars is done assuming that cross-sections remain plane after bending.

The joint surfaces for concreting must be roughened at least to such an extent that aggregates protrude.

The accessory list in this report is for the information of the user only. All the relevant installation conditions (drilling, cleaning, setting) must be done in accordance with the relevant UKTA and product IFUs.

If the design is carried out assuming a simply supported connection a check for partial fixity may be required, acc. to EN1992-1-1.

No shear check verification was selected by the user, the verification was not performed in PROFIS Engineering.

Interface meets the design criteria!

| | | | |
|--------------------|---------------------|------------|------------|
| Company: | | Page: | 14 |
| Address: | | Specifier: | |
| Phone Fax: | | E-mail: | |
| Design: | Rebar - 11 Jan 2024 | Date: | 11.01.2024 |
| Rebar application: | | | |

6. Installation data

Mortar: HIT-RE 500 V4 + Rebar

Item number: 2287557 HIT-RE 500 V4 (adhesive)

Reinforcement yield strength f_{yk} : 500.00 N/mm²

Drilling method: Hammer drilling (HD) (Drilling aid is used)

Hole type: Dry Concrete

Installation temperature: from 5°C to 20°C

Roughness: Rough

Top layer 1

Rebar diameter: 32mm

Number of bars: 3

Top cover: 129 mm

Drill length, l_v : 320 mm

Drill diameter, d_0 : 40 mm

Hole cleaning: Compressed air without brushing or Cleaning with the air nozzle

Top layer 2

Rebar diameter: 32mm

Number of bars: 3

Top cover: 148 mm

Drill length, l_v : 320 mm

Drill diameter, d_0 : 40 mm

Hole cleaning: Compressed air without brushing or Cleaning with the air nozzle

Bottom layer 1

Rebar diameter: 32mm

Number of bars: 3

Bottom cover: 149 mm

Drill length, l_v : 584 mm

Drill diameter, d_0 : 40 mm

Hole cleaning: Compressed air without brushing or Cleaning with the air nozzle

| | | | |
|--------------------|---------------------|------------|------------|
| Company: | | Page: | 15 |
| Address: | | Specifier: | |
| Phone Fax: | | E-mail: | |
| Design: | Rebar - 11 Jan 2024 | Date: | 11.01.2024 |
| Rebar application: | | | |

Bottom layer 2

Rebar diameter: 32mm

Number of bars: 3

Bottom cover: 148 mm

Drill length, l_v : 584 mm

Drill diameter, d_0 : 40 mm

Hole cleaning: Compressed air without brushing or Cleaning with the air nozzle

6.1. Working time and curing time ^{1) 2)}

| Temperature in the base material T | Maximum working time t_{work} | Initial curing time $t_{cure,ini}$ | Minimum curing time t_{cure} |
|---------------------------------------|------------------------------------|---------------------------------------|-----------------------------------|
| -5 °C to -1 °C | 2 hours | 2 days | 7 days |
| 0 °C to 4 °C | 2 hours | 1 days | 2 days |
| 5 °C to 9 °C | 2 hours | 16 hours | 1 days |
| 10 °C to 14 °C | 1.5 hours | 12 hours | 16 hours |
| 15 °C to 19 °C | 1 hours | 8 hours | 16 hours |
| 20 °C to 24 °C | 30 min | 4 hours | 7 hours |
| 25 °C to 29 °C | 20 min | 3.5 hours | 6 hours |
| 30 °C to 34 °C | 15 min | 3 hours | 5 hours |
| 35 °C to 39 °C | 12 min | 2 hours | 4.5 hours |
| 40 °C | 10 min | 2 hours | 4 hours |

1) The curing time data are valid for dry base material only. In wet base material the curing times must be doubled.

2) The minimum temperature of the foil pack is +5°C.

| | | | |
|--------------------|---------------------|------------|--------------|
| Company: | | Page: | 16 |
| Address: | | Specifier: | |
| Phone Fax: | | E-mail: | |
| Design: | Rebar - 11 Jan 2024 | Date: | 11. 01. 2024 |
| Rebar application: | | | |

7. Remarks; Your cooperation duties

Any and all information and data contained in the Software concern solely the use of Hilti products and are based on the principles, formulas and security regulations in accordance with Hilti's technical directions and operating, mounting and assembly instructions, etc. that must be strictly complied with by the user. All figures contained therein are average figures, and therefore use-specific tests are to be conducted prior to using the relevant Hilti product. The results of the calculations carried out by means of the Software are based essentially on the data you put in. Therefore, you bear the sole responsibility for the absence of errors, the completeness and the relevance of the data to be put in by you. Moreover, you bear sole responsibility for having the results of the calculation checked and cleared by an expert, particularly with regard to compliance with applicable norms and permits, prior to using them for your specific facility. The Software serves only as an aid to interpret norms and permits without any guarantee as to the absence of errors, the correctness and the relevance of the results or suitability for a specific application.

You must take all necessary and reasonable steps to prevent or limit damage caused by the Software. In particular, you must arrange for the regular backup of programs and data and, if applicable, carry out the updates of the Software offered by Hilti on a regular basis. If you do not use the AutoUpdate function of the Software, you must ensure that you are using the current and thus up-to-date version of the Software in each case by carrying out manual updates via the Hilti Website. Hilti will not be liable for consequences, such as the recovery of lost or damaged data or programs, arising from a culpable breach of duty by you.