

**Hilti Saudi Arabia for Const. Tools**

King Abdul Aziz Street
P.O. Box 5287 | Riyadh 11422
T +966 1 460 8974
F +966 1 460 6255
Toll Free 8001200013
www.hilti.com

CR 1010278712
LLC Paid up capital SAR 39,230,000

شركة هيلتي العربية السعودية لأدوات البناء
شارع الملك عبد العزيز
صندوق بريد 5287 الرياض 11422
تلفون +966 1 460 8974
فاكس +966 1 460 6255
الرقم المجاني 8001200013
www.hilti.com

سجل تجاري رقم 1010278712
شركة ذات مسؤولية محدودة - رأس المال المدفوع 39,230,000 ريال سعودي

Date : February 18, 2018

To whom it may concern,

We, Hilti Saudi Arabia for Const. Tools would like to confirm that HILTI Threaded Anchor Rod HDG (grade 8.8) consist of the same material of HIT-V HDG (grade 8.8) Anchor Rod and can perform as alternative rod when used with Hilti Adhesive Anchors (HIT)

Due to our best knowledge cutting of Galvanized Rods do not influencing mechanical properties, but leads to removal of coating in the cutting point. That's why it is recommended to use cold cutting methods to minimize adverse effect to the coating (for example SCM 22-A Cutting Tool).

Also, we recommend implementing necessary actions for re-applying zinc coating to the cut surface (e.g. zinc spray MZN-400). Cut end of threaded rod recommended to place into the concrete hole (downside), because outer (upper) end of threaded rod usually influenced by much more powerful corrosion factors than inner one.

Under any circumstances installer need to carefully assess corrosion factors, available means for zinc coating re-applying and made comprehensive decision about applicability of above mentioned workflow.

Anchor Product Manager
Osama Zein

Hilti Saudi Arabia

Kilo 14 | King Fahd Street | P. O. Box 15930
Jeddah 21512 | Saudi Arabia
sa.tso@hilti.com



**Hilti Saudi Arabia for Const. Tools**

King Abdul Aziz Street
P.O. Box 5287 | Riyadh 11422
T +966 1 460 8974
F +966 1 460 6255
Toll Free 8001200013
www.hilti.com

CR 1010278712
LLC Paid up capital SAR 39.230.000

شركة هيلتي العربية السعودية لأدوات البناء

شارع الملك عبد العزيز
صندوق بريد 5287 الرياض 11422
تلفون +966 1 460 8974
فاكس +966 1 460 6255
الرقم المجاني 8001200013
www.hilti.com

سجل تجاري رقم 1010278712
شركة ذات مسؤولية محدودة - رأس المال المدفوع 39,230,000 ريال سعودي

Date : February 21, 2018

Company Name : Arabian Construction Company

To whom it may concern,

We, Hilti Saudi Arabia for construction tools would like to confirm that HILTI Threaded Anchor Rod consist of the same material of HIT-V Anchor Rod and can perform as alternative rod when used with Hilti Adhesive Anchors (HIT)

Due to our best knowledge cutting of Galvanized Rods do not influencing mechanical properties, but leads to removal of coating in the cutting point. That's why it is recommended to use cold cutting methods to minimize adverse effect to the coating (for example SCM 22-A Cutting Tool).

Also, we recommend implementing necessary actions for re-applying zinc coating to the cut surface (e.g. zinc spray MZN-400).

Under any circumstances installer need to carefully assess corrosion factors, available means for zinc coating re-applying and made comprehensive decision about applicability of above mentioned workflow.

Anchor Product Manager
Osama Zein

Hilti Saudi Arabia

Kilo 14 | King Fahd Street | P. O. Box 15930
Jeddah 21512 | Saudi Arabia
sa.tso@hilti.com

